








# SXP Floodlight Series



Explosion Proof • UL 844 & 1598A • Marine Outside Type • Factory Sealed

## Components and Accessories

Outlet Boxes	Description	Hub Size (In.)	Catalog Number	Shipping Weight (Lbs.)
	Pendant	3/4 1	<b>SXPP</b> <b>SXPP1</b>	2.15 2.15
	Ceiling	3/4 1	<b>SXPC</b> <b>SXPC1</b>	4.0 4.0
	Wall	3/4 1	<b>SXPW</b> <b>SXPW1</b>	6.20 6.20
	Stanchion	1-1/4 1-1/2	<b>SXPS</b> <b>SXPS1</b>	3.20 3.20

Globes and Guards	Description	Catalog Number	Shipping Weight (Lbs.)
	Prismatic Glass Globe Assembly for 70-150W HPS, 175-250W MH	<b>SXP25GL</b>	6.50
	Prismatic Glass Globe Assembly for 250-400W HPS and 400W MH	<b>SXP40GL</b>	9.40
	Stainless Steel Wire Guard for 70-150W HPS, 175-250W MH	<b>SXP25WG</b>	1.50
	Stainless Steel Wire Guard for 250-400W HPS, 400W MH	<b>SGU40SS</b>	2.25

Reflectors	Description	Catalog Number	Shipping Weight (Lbs.)
	Standard Dome Reflector Fiberglass Filled Polymeric	<b>SR40D</b>	3.00
	30° Angle Reflector Fiberglass Filled Polymeric	<b>SR40A</b>	4.50
	High Bay Aluminum Reflector with Baked on White Enamel	<b>SR40HB</b>	5.00

Connector Blocks and Sockets	Description	Catalog Number	Shipping Weight (Lbs.)
	Replacement Female Connector Block (for Outlet Boxes 70-400W)	<b>26641</b>	1.00
	Replacement Socket 70-400W	<b>70043</b>	1.50