

XPS LED SERIES

Explosionproof edge lit LED multipurpose sign

Key Features

- Emergency battery back-up integral to sign (no additional enclosure required)
- 3-hour emergency operation
- Optional battery back-up self-diagnostic feature
- Field replaceable LED circuit boards and drivers with quick disconnects
- Edge-lit sign



Classifications

- Class I, Division I, Groups C & D
- Class II, Division I, Groups E, F & G
- Class III
- Class I, Zone I, Groups IIA, IIB,
- Zone 2, Groups IIA, IIB + H2 & IIC
- UL 844, UL 8750 & UL 924
- ULI598A Marine Outside Type
- Temperature Class (T-Rating)-T6
- Patent No. 7,287,347
- IP65

Standard Materials

Body: A356T6 aluminum
(less than .4% copper content)
with baked-on gray epoxy finish

Gasket: One-piece silicone

Sign: Acrylic

Hardware: Stainless steel

Additional Features

- Wall, pendant and end mounting options
- Custom colors and languages available
- Single- or double-sided option
- Sealed NiCad batteries
- Provided with three (3) ½" NPT hubs
- Red or green LED options



XPS 2 - G - DT - WP - XX

1 2 3 4 5 6

1
SERIES
 XPS LED*
 *Customer must specify sign color and

2
NUMBER OF FACES
 1 = Single Face
 2 = Double Face

3
LEGEND COLOR
 A = Amber
 B = Blue
 R = Red

G = Green
 X = Other (Contact Factory)

4
VOLTAGE/FREQUENCY
 DT = 120/277V 60 HZ
 24 = 220-240V 50/60 HZ
 Other voltages available- consult factory

5
MOUNTING
 WP = Wall/Pendant Mounting
 EB = End Bracket

6
OPTIONS¹
 EM = Emergency Battery Backup
 X = Specify Legend (Cannot Say EXIT)

¹ Consult factory for pricing.

Part numbering logic is for explaining part number structure only. Not all combinations are possible; consult factory for catalog numbers not listed on chart..